HOLCIM

2024 Bungendore Quarry Pollution Incident Response Management Plan

ember 202

Pollution Incident Response Management Plan Bungendore

and C

Bungendore Quarry Pollution Incident Response Management Plan (PIRMP)

Revision/ Checking History

Revision Number	Date	Checked by	Issued by
1	23/9/2014	Daniel Lidbetter– NSW/ACT Planning & Environment Coordinator Peter Bujaroski - Quarry Manager	Daniel Lidbetter
2	2015	Daniel Lidbetter – NSW/ACT Planning & Environment Coordinator Peter Bujaroski - Quarry Manager	Daniel Lidbetter
3	2016	Daniel Lidbetter – NSW/ACT Planning & Environment Coordinator Robert Hewson – Quarry Manager	Daniel Lidbetter
4	2017	Amy Nelson – NSW/ACT Planning & Environment Coordinator Robert Hewson – Quarry Manager	Amy Nelson
5	Oct 2018	Hema Vignaraja – SHE Reporting Analyst Robert Hewson – Quarry Manager	Hema Vignaraja
6	June 2022	Hema Vignaraja – SHE Reporting Analyst Shilpa Shashi - NSW/ACT Planning & Environment Coordinator	Hema Vignaraja
7	November 2022	Hema Vignaraja – SHE Reporting Analyst Rob Townsend - Acting Environment Manager NSW	Hema Vignaraja

8	November 2023	Robert Hewson - Quarry Manager	Dozie Egeonu Environment Manager - NSW & ACT
7	November 2024	Robert Hewson - Quarry Manager	Dozie Egeonu Environment Manager - NSW & ACT

Table of Contents

1.	Purpose	4
2.	Scope	6
3.	Definitions	6
4.	Associated Documentation	6
5.	Responsibility	6
6.	Record Retention	7
7.	Procedure	7
7.1	Environmental Impact and Hazard Register	7
	Table 1: Holcim SHE Risk Score Matrix – Attachment 6.2F	8
	Table 2: Holcim Quarry Environmental Impact and Hazard Register	10
7.2	Pollutant and Safety Equipment Information	16
7.3	Emergency Response Map	31
7.4	PIRMP Review	32
7.5	Typical Holcim Response process	33
7.6	Communication Strategy	35
8	Staff Training	36
9	Continual Improvement	36

Appendices

- A Emergency Contact Details
- B Pollution Incident Response Test Checklist
- C Community Notification Strategy
- D Maps

Glossary of Acronyms

PIDS- Pollution Info	ormation Data Sheet
----------------------	---------------------

- PPE- Personal Protective Equipment
- SDS- Safety Data Sheets
- PEOA- Protection of the Environment Operations Act 1997

1. Purpose

The purpose of this document is to detail the pollution incident response management plan for the **Bungendore Sand Quarry** to comply with Section 5.7A of the Protection of the Environment Operations (POEO) Act:

Protection of the Environment Operations Act 1997 No 156

Part 5.7A Duty to prepare and implement pollution incident response management plans

153A Duty of licence holder to prepare pollution incident response management plan

The holder of an environment protection licence must prepare a pollution incident response management plan that complies with this Part in relation to the activity to which the licence relates.

Maximum penalty:

- (a) in the case of a corporation—\$1,000,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues, or
- (b) in the case of an individual—\$250,000 and, in the case of a continuing offence, a further penalty of \$60,000 for each day the offence continues.

153B EPA may direct other persons to prepare pollution incident response management plan

- (1) The EPA may, in accordance with the regulations, require the occupier of premises at which industry is carried out to prepare a pollution incident response management plan that complies with this Part in relation to activities at the premises.
- (2) A person must not fail to comply with such a requirement.

Maximum penalty:

- (a) in the case of a corporation—\$1,000,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues, or
- (b) in the case of an individual—\$250,000 and, in the case of a continuing offence, a further penalty of \$60,000 for each day the offence continues.
- (3) The regulations may make provision for or with respect to:
 - (a) the class or classes of premises, or industries carried out at premises, that may be the subject of a requirement to prepare a pollution incident response management plan, and
 - (b) the circumstances in which some or all premises within those classes may be the subject of a requirement to prepare a pollution incident response management plan.

153C Information to be included in plan

A pollution incident response management plan must be in the form required by the regulations and must include the following:

(a) the procedures to be followed by the holder of the relevant environment protection licence, or the occupier of the relevant premises, in notifying a pollution incident to:

- (i) the owners or occupiers of premises in the vicinity of the premises to which the environment protection licence or the direction under section 153B relates, and
- (ii) the local authority for the area in which the premises to which the environment protection licence or the direction under section 153B relates are located and any area affected, or potentially affected, by the pollution, and
- (iii) any persons or authorities required to be notified by Part 5.7,
- (b) a detailed description of the action to be taken, immediately after a pollution incident, by the holder of the relevant environment protection licence, or the occupier of the relevant premises, to reduce or control any pollution
- (c) the procedures to be followed for co-ordinating, with the authorities or persons that have been notified, any action taken in combating the pollution caused by the incident and, in particular, the persons through whom all communications are to be made,
- (d) any other matter required by the regulations.

153D Keeping of plan

A person who is required to prepare a pollution incident response management plan under this Part must ensure that it is kept at the premises to which the relevant environment protection licence relates, or where the relevant activity takes place, and is made available in accordance with the regulations.

Maximum penalty:

- (a) in the case of a corporation—\$1,000,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues, or
- (b) in the case of an individual—\$250,000 and, in the case of a continuing offence, a further penalty of \$60,000 for each day the offence continues.

153E Testing of plan

A person who is required to prepare a pollution incident response management plan under this Part must ensure that it is tested in accordance with the regulations.

Maximum penalty:

- (a) in the case of a corporation—\$1,000,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues, or
- (b) in the case of an individual—\$250,000 and, in the case of a continuing offence, a further penalty of \$60,000 for each day the offence continues.

153F Implementation of plan

If a pollution incident occurs in the course of an activity so that material harm to the environment (within the meaning of section 147) is caused or threatened, the person carrying on the activity must immediately implement any pollution incident response management plan in relation to the activity required by this Part.

Maximum penalty:

(a) in the case of a corporation—\$2,000,000 and, in the case of a continuing offence, a further penalty of \$240,000 for each day the offence continues, or

(b) in the case of an individual—\$500,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues.

2. Scope

The scope of this management plan includes:

Pollution Incident Response Management Plan (PIRMP) for environmental pollution generated at the Bungendore Sand Plant;

3. Definitions

Pollution Incident -	An incident or set of circumstances during or as a consequence of which there is or is likely to be a leak, spill or other escape or deposit of a substance, as a result of which pollution has occurred, is occurring or is likely to occur. It includes an incident or set of circumstances in which a substance has been placed or disposed of on premises, but it does not include an incident or set of circumstances involving only the emission of any noise.
Material Harm -	(i) it involves actual or potential harm to the health or safety of human beings or to ecosystems that is not trivial, or
	(ii) it results in actual or potential loss or property damage of an amount, or amounts in aggregate, exceeding \$10,000 (or such other amount as is prescribed by the regulations), It does not matter that harm to the environment is caused only in the premises where the pollution incident occurs, and
Loss -	the reasonable costs and expenses that would be incurred in taking all reasonable and practicable measures to prevent, mitigate or make good harm to the environment.

4. Associated Documentation

- Protection of the Environment Operations Act 1997
- Protection of the Environment (General) Amendment (Pollution Incident Response Management Plans) Regulation 2012
- Appendix A: Emergency Contact Details
- Appendix B: Pollution Incident Response Test Checklist
- Appendix C: Community Notification Strategy

5. Responsibility

The following personnel are responsible for the PIRMP;

- 1) Activating the plans and managing the response: Robert Hewson Quarry Manager
- 2) Notifying and coordinating relevant authorities: Robert Croxon Quarry Supervisor
- 3) Implementation and management of this document: Quarry Manager/ Site Supervisor
- 4) Annual review and test of the PIRMP: NSW/ACT Planning & Environment Coordinator

6. Record Retention

A copy of all Quarry pollution incident response records will be retained on site in accordance with SHE guideline 1.4 – Administrative and Legal Requirements. A copy will also be saved electronically on google drive in the 'Site PIRMPs 2022 Final' folder that will be shared with the site.

Records must be made available to EPA officers and any person responsible for the PIRMP.

7. Procedure

The following section outlines the management procedures for pollution incident response management. The protocol is split into three sections:

- 1) Eliminating and/or Avoiding Generation of Pollution
- 2) Management of Pollution Incidents
- 3) Improving and Reviewing Pollution Incident Response Management Plan

7.1 Environmental Impact and Hazard Register

In order to effectively plan for a potential pollution event, a register of environmental hazards has been created. Each hazard has been assessed in accordance with the Holcim SHE Risk Assessment tool (see Table 1 below).

The hazards have been grouped according to the area of environmental impact. By identifying these hazards ahead of time, mitigation measures can be identified and implemented through site procedures to minimise the risk of a pollution event occurring (table 2 below).

Table 1: Holcim SHE Risk Score Matrix – Attachment 6.2F

Step 1 - Consider the Consequence												
What are the consequences of the most reasonable worst case scenario considering a credible failure of existing controls?												
Consequence	Disaster	Severe	Serious	Significant	Minor							
Environment On Site & Off Site	Major event, unconfined impact, severe permanent damage with low likelihood of recovery.	Significant permanent damage; reversible damage with recovery time of years; high potential for prosecution	Minor permanent damage; temporary damage that is widespread or that has moderate impact	Damage that is near source confined, temporary and minor	No measurable damage to environment							
Compliance With Legal and Other Requirements	Blatant or serious breach of legal requirement, leading to operation being suspended or severely reduced. Prosecution expected.	Breach of external requirement (license, legislation, regulation, contract etc) with high potential for prosecution and/or high impact.	Non-compliance with external requirement with moderate potential for impact.	Repeated non-compliance with internal procedure, non-compliance with external requirement with low potential impact	Minor non-compliance with interna procedures.							
Community Perception and Reputation	Significant adverse media attention (state or national level), loss of reputation or work nationally or across product groups.	Prosecution, significant impacts on social license to operate, loss of reputation or ability to secure work across product groups.	Local adverse media attention, loss of reputation or ability to secure work in local area, complaints that result in changes to external requirements.	Multiple community complaints or complaints that require changes to internal operating procedures.	Community complaint resolved wi no changes to existing operating procedures.							

Note: Temporary environmental damage has a duration of up to approximately one week to rectify

Step 2 - Consider the Likelihood											
What is the likelihood that the proposed consequence will occur with a credible failure of existing controls?											
Likelihood	Certain	Likely	Possible	Unlikely	Rare						
Description	Event that is expected to occur on multiple occasions	Event that is likely to occur at least once	Event that may occur	Event that is unlikely to occur	Event that may occur only in exceptional circumstances						

Frequency	Event is likely to occur more than twice a year.	Event is likely to occur once or twice a year.	Event is likely to occur more than once or twice in a 10 year period	Event is likely to occur once or twice in a 10 year period	Event is likely to occur once or twice in a 100 year period

Step 3 - Determine Risk Rating from the Risk Matrix												
Likelihood	Consequences											
LINEIMOOU	Disaster	Severe	Serious	Significant	Minor							
Certain	High	High	High	Medium	Medium							
Likely	High	High	Medium	Medium	Low							
Possible	High	Medium	Medium	Low	Low							
Unlikely	Medium	Medium	Low	Low	Low							
Rare	Medium	Low	Low	Low	Low							

Table 2: Holcim Quarry Environmental Impact and Hazard Register

		Risk			Mitigation Measures	Revised Risk		
Ne	Key Environmental Hazards		с	R			с	R
Α	ir Quality							
1	Excessive dust emissions	P o s i b I e	S e r i o u s	M e d i u m	 Complete monitoring & assess results quarterly Review results & monitoring program quarterly Water carts/spraying Minimise disturbed areas Stop dust generating activities as necessary Progressively rehabilitate disturbed areas Dust minimisation training 	U n i k e I y	S i g n i f i c a n t	L O W
2	Health issues off site	R a r e	S e v e r e	L o w	 As per (1) Complaints hot line Issue monitoring results Communicate construction activities to neighbours plus potential for dust 	R a r e	S e r i o u s	L o w

8	Equipment exhaust emissions exceed limits	Un I k I Y	S i g n i f c a n t	L o W	 Inspect equipment engine emissions regularly All equipment is serviced and maintained to OEM requirements Excessive equipment emissions to trigger out of service procedures 	R a r e	S i g n i f i c a n t	L o w
1	roundwater contamination	Unlikel y	S e r u s	L o w	 Ensure storage, handling and transport of dangerous goods are conducted in accordance with Australian Standards Identify, classify, quantify & appropriately store hazardous waste Develop & implement oil & fuel spillage controls Ensure hazardous waste is minimised Licenced contractors to remove hazardous waste from site Keep records of all hazardous waste movements Develop & implement oil & fuel spillage controls Implement bunding to appropriate areas Ensure adequate spill kits are available on site including adequate training Minimise hazardous waste storage quantities on site 	R a r e	S e r i o u s	L O W
2	Lowering of groundwater table	R a r e	S e r i o	L o w	 Monitor & report on ground water levels Comply with Water Management Plan water balance 	R a r e	S i g n i	L o w

3 5 1	Acid-sulphate soils Inface Water Discharge of sediment	L i k e I y P o s s i b I e	u s s e r i o u s s e r i o u s	M e d i u m M e d i u m	 Acid sulphate status is known Implement acid-sulphate management plan Regular review of acid-sulphate management plan outcomes Monitor tailings to ensure they are contained and return water is suitable for processing Maintain flocculation system Implement dust control procedures as per AIR 	U n l k e l y U n l i k e l y	f i c a n t S e r i o u s S e r i o u s	L o w L o w
2	Discharge of hazardous materials	R a r e	S e v e r e	L o W	 As per (1) Ensure storage, handling and transport of dangerous goods are conducted in accordance with relevant Australian Standard Identify classify, quantify & appropriately store hazardous waste Develop & implement oil & fuel spillage controls Implement bunding to appropriate areas Ensure adequate spill kits are available on site including adequate training for effective use Minimise hazardous waste storage quantities on site 	R a r e	S e i o u s	L o w

		<u> </u>				-	<u> </u>	
					 Appropriate location of hazardous materials storage areas to prevent off-site discharges 			
E	cology							
1	Damage to local flora	P o s i b I e	S e r i o u s	M e d i u m	 Develop & implement Biodiversity Action Plan Put in adequate physical protection measures including signage Monitor & report on site flora health regularly Suitable training re flora protection Removal of stock from sensitive areas Implement bushfire hazard reduction tasks Removal of feral animals from sensitive areas Noxious weed control in sensitive areas 	Un li k e J y	S i g n i f i c a n t	L o w
2	Damage to site fauna	U n i k e I v	S e r i o u s	R a r e	 As per (1) Information re local WIRES for distressed or injured fauna 	R a r e	S e r i o u s	L o w
3	Dust pollution onto site sensitive ecological areas	U n l k e l y	S e v e r e	M e d i u m	 As per (1) Comply with site Management Plans Regular review of riparian areas (as per Management Plans) 	U n i k e I y	S i g n i f i c a n t	L o w

La	Ind							
1	Spill of liquid fuel whilst in storage	P o s i b I e	S e v e r e	M e d i u m	 Fuels stored according to Holcim's bunding requirements. Measures in place to ensure spills do not leave site boundaries ie diverting flow away from boundaries, stormwater drains. Bunding subject to regular inspection and maintenance 	S i g n i f i c a n t	Unli kel y	L o w
2	Spill during delivery of fuel to mobile equipment	P o s i b l e	S e v e r e	M e d i u m	 Breakaway couplings installed on mobile fuel delivery vehicles. Drivers stay with vehicle during refuelling Emergency spill kits located on fuel delivery vehicles. Spill response equipment is regularly inspected and maintained Mobile refuelling takes place in the pit Drivers trained in spill response procedures. Refuelling takes place in designated refuelling areas. 	U n i k e I y	S i g n i f c a n t	L o w
3	Spill during delivery of fuel to storage tank	P o s i b I e	S e v e r e	M e d i u m	 Supplier's fuel transfer procedure is known Fuel transfer is supervised against suppliers procedure 	U n l k e l y	S i g n i f i c a n t	L o w

7.2 Pollutant and Safety Equipment Information

Legislative requirements under the Protection of the Environment Operations (POEO) Act dictate that the site is to provide information for all pollutants that are used and stored on the site. This information is required as it assists personnel responsible for coordinating spill responses to more effectively manage spills.

This information must be presented as a manifest detailing the pollutants stored at the site, the location of these storage areas, and the safety equipment to be made available at these areas. A Pollution Information Data Sheet (PIDS) has been prepared that includes the following information for each pollutant. Refer to table 3 below

- The intended use for the pollutant
- How the pollutant is stored
- SDS information
- Safety equipment or other devices that are used to minimise the risks to human health or the environment and to contain or control a pollution incident
- PPE needed to safely manage a spill of the pollutant
- Procedure for cleaning up a spill of the pollutant.

In order to ensure the currency and reliability of the information in the PIDS, the information should be reviewed and updated on a monthly basis.

Table 3: Pollutant Information Data Sheet and clean-up methods

Pollutant	Storage Location	Current SDS held Yes/No	Emission control equipment ₍₁₎	PPE (1)	Spill Clean Up Method (1)
Fuel	Fuel Storage Tank	Yes	Sand, earth, vermiculite	PVS gloves, safety glasses, goggles	Large Spill
					Assess
					Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard Post a guard or barricade Can you stop the source of the spill?
					Ensure Personal Safety First priority is to ensure safety of yourself and others
					in the area Consider evacuation and isolation. Do you or others require PPE Check Safety Data Sheet
					Secure
					Secure the spill If hazardous to public or other staff exists Post a guard immediately Enter barricades to prevent unintended access

		Contain
		Contain the spill quickly by surrounding with the booms which should be firmly secured in place. Find the source of the leak and stop it Emergency stop, cap, plug, move, adjust Move other containers from that area to a bunded area In the case of spillage on water, prevent the spread of
		product by the use of suitable barrier equipment. Prevent Prevent spillage to stormwater drains and entry into sewer, water courses, basements or confined areas.
		Absorb
		Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation.
		Recover product from the surface.
		Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor
		Disposal
		Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or

					diatomaceous earth and place into a container according to local legislation. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked and placed in a leak proof container which is locked. SDS should be made available.
					Reporting Incident and Corrective and Preventative action should be captured on the ICARE. Small Spill
					Stop leak without risk. Move containers from spill area Absorb with an inert material and place in appropriate waste disposal container.
					Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
Lubricants	Lubricant Storage Facility	Yes	Sand, earth, vermiculite, barrier equipment (booms, floats etc.)	PVC Gloves, safety glasses, goggles	Large Spill

		Assess
		Quickly assess the spill:
		Decide whether to handle the situation by yourself or
		if you require help.
		Advise your team of the hazard
		Post a guard or barricade
		Can you stop the source of the spill?
		Ensure Personal Safety
		First priority is to ensure safety of yourself and others
		in the are
		Consider evacuation and isolation.
		Do you or others require PPE
		Check Safety Data Sheet
		<u>Secure</u>
		Secure the spill
		If hazardous to public or other staff exists
		Post a guard immediately
		Enter barricades to prevent unintended access
		<u>Contain</u>
		Contain the spill quickly by surrounding with the
		booms which should be firmly secured in place.
		Find the source of the leak and stop it
		Emergency stop, cap, plug, move, adjust

		Move other containers from that area to a bunded area
		In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment.
		<u>Prevent</u>
		Prevent spillage to stormwater drains and entry into sewer, water courses, basements or confined areas.
		Absorb
		Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation.
		Recover product from the surface.
		Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor
		Disposal
		Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation.
		Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor.

					Contaminated absorbent material may pose the same hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked and placed in a leak proof container which is locked. SDS should be made available. Reporting Incident and Corrective and Preventative action should be captured on the ICARE. Small Spill Stop leak without risk. Move containers from spill area Absorb with an inert material and place in appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
Vehicle fluids	Oil Storage Facility	Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	 Large Spill In the case of large spills contact relevant personnel Stop leak without risk. Move containers from spill area. Approach the release from upwind
					5) Prevent entry into sewer, water courses, basements or confined areas.

					6) Wash spillages into an effluent treatment plant or
					proceed as follows.
					7) Contain and collect spillage with
					non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and
					place into a container according to local
					legislation.
					 Contaminated absorbent material may pose the same hazard as the spilt product
					Small Spill
					1) Stop leak without risk.
					2) Move containers from spill area
					3) Dilute with water and mop up, or absorb with an
					inert dry material and place in appropriate waste disposal container
					4) Dispose of via a licensed waste disposal
					contractor.
Vehicle Wash &	Shipping storage	Voc	Sand, earth, vermiculite	PVC Gloves, safety glasses	Large Spill
Vehicle Wash & Degreaser	Shipping storage container	Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Large Spill Assess
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Assess
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Assess Quickly assess the spill:
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Assess Quickly assess the spill: Decide whether to handle the situation by yourself or
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Assess Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard Post a guard or barricade
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Assess Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Assess Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard Post a guard or barricade
		Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses	Assess Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard Post a guard or barricade Can you stop the source of the spill?

		Consider evacuation and isolation.
		Do you or others require PPE
		Check Safety Data Sheet
		Check Salety Data Sheet
		<u>Secure</u>
		Secure the spill
		If hazardous to public or other staff exists
		Post a guard immediately
		Enter barricades to prevent unintended access
		Contain
		Contain the spill quickly by surrounding with the
		booms which should be firmly secured in place.
		Find the source of the leak and stop it
		Emergency stop, cap, plug, move, adjust
		Move other containers from that area to a bunded
		area
		In the case of spillage on water, prevent the spread of
		product by the use of suitable barrier equipment.
		product by the use of suitable barrier equipment.
		Durauset
		<u>Prevent</u>
		Prevent spillage to stormwater drains and entry into
		sewer, water courses, basements or confined areas.
		Absorb
		Contain and collect spillage with non-combustible,
		absorbent material e.g. sand, earth, vermiculite or

		diatomaceous earth and place into a container
		according to local legislation.
		Recover product from the surface.
		Use spark-proof tools and explosive proof equipment.
		Dispose of via a licensed waste disposal contractor
		<u>Disposal</u>
		Contain and collect spillage with non-combustible,
		absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container
		according to local legislation.
		Use spark-proof tools and explosive proof equipment.
		Dispose of via a licensed waste disposal contractor.
		Contaminated absorbent material may pose the same
		hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked
		and placed in a leak proof container which is locked.
		SDS should be made available.
		Reporting
		Incident and Corrective and Preventative action
		should be captured on the ICARE.
		Small Spill
		Stop leak without risk.

					Move containers from spill area Dilute with water and mop up, or absorb with an inert dry material and place in appropriate waste disposal container Dispose of via a licensed waste disposal
Hardeners and Resins	Fixed Plant Workshop	No	Sand, earth, vermiculite	Safety glasses, PVC gloves, Respirator	contractor. Major Spills Large Spill Assess Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard Post a guard or barricade Can you stop the source of the spill? Ensure Personal Safety First priority is to ensure safety of yourself and others in the area Consider evacuation and isolation. Do you or others require PPE
					Check Safety Data Sheet

	Secure the spill
	If hazard to public or other staff exists
	Post a guard immediately
	Enter barricades to prevent unintended access
	Contain
	Contain the spill quickly by surrounding with the
	booms which should be firmly secured in place.
	Find the source of the leak and stop it Emergency
	stop, cap, plug, move, adjust
	Move other containers from that area to a bunded
	area
	In the case of spillage on water, prevent the spread of
	product by the use of suitable barrier equipment.
	Prevent
	Prevent spillage to stormwater drains and entry into
	sewer, water courses, basements or confined areas.
	Absorb
	Contain and collect spillage with non-combustible,
	absorbent material e.g. sand, earth, vermiculite or
	diatomaceous earth and place into a container
	according to local legislation.
	Recover product from the surface.

		Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor
		Disposal
		Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation.
		Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor.
		Contaminated absorbent material may pose the same hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked and placed in a leak proof container which is locked. SDS should be made available.
		Reporting
		Incident and Corrective and Preventative action should be captured on the ICARE.
		Minor Spills
		Contain spillage
		Avoid breathing vapours and contact with skin and eyes
		Control contact using PPE

					Contain and absorb with sand, earth, inert material, vermiculite etc. Small spills should be covered with inorganic absorbents and disposed of properly. Organic absorbents (ie. sawdust) may ignite when contaminated with amines in closed containers
Oils	Oil Storage Facility	Yes	Sand, earth, vermiculite	Safety glasses, PVC gloves	 Protective Measures Eliminate all sources of ignition in vicinity of spilled material. Spill Management Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.
Dry Powders		No	Access to council sweeper, soil, sand, vermiculite	Safety glasses, PVC Gloves,	Accidental Release Measures Emergency procedures: Prevent entry to area by unprotected personnel.

	Fixed Plant Workshop				 Methods and material for containments and clean up 1) Vacuum or wet sweep material avoiding generation of dusts. 2) A fine water spray should be used to suppress dust when sweeping. 3) Product dampened with water may be collected with a clean shovel. 1) Seal all spilled product and wastes in vapour tight labelled plastic containers for reuse/recycle where possible or eventual disposal.
Welding gas	Fixed Plant Workshop – External welding gas storage cages	Yes	Ventilation	Respirator	 <u>Occupational Release:</u> 1) Avoid heat, flames, sparks and other sources of ignition. 2) Stop leak if possible without personal risk. 3) Reduce vapours with water spray 4) Keep unnecessary people away, isolate hazard area and deny entry. 5) Remove sources of ignition. 4) Ventilate closed spaces before entering.
Effluent	Septic tank treatment adjacent to amenities building	No	Access to council commercial vacuum/ pump truck,, soil, sand, bleach, hydrated lime	PVC Gloves, goggles, overalls	 <u>Accidental Release Measures</u> 1) Contaminated area must be clearly marked or cordoned off to restrict access. 2) Protective clothing should be worn when cleaning up a sewage spill. 3) If the spilled material can't be recovered using hand tools, a commercial vacuum / pump truck should be called to remove all visible liquid and solid material. 4) When the area is visibly clean, either a chlorine / water solution or hydrated lime should be applied to the spill area to disinfect. 5) If a major spill has occurred hydrated lime should be applied to the area in place of chlorine bleach

			 6) .Enough hydrated lime should be applied to raise the pH to at least 12. By raising the pH to 12 for at least 1 hour, the area will be disinfected. 1) Because lime is a caustic material, access to the area treated with lime must be restricted during the disinfection period.
--	--	--	---

(1) This information should be drawn from a review of the SDS or manufacturer/supplier technical information


7.3 Emergency Response Map

In addition to the PIDS the site needs to prepare an emergency response map that provides the following information;

- address of site
- location of pollutant storage
- location of safety equipment
- emergency evacuation / muster points
- stormwater drains / flow paths
- sensitive receivers
- sediment dam overflow locations
- location of SDS
- surrounding area that is likely to be affected by a pollution incident
- discharge location of stormwater drains to nearest water coarse or water body

Existing site maps that have been developed to comply with Holcim SHE system requirement 1.84 may be used if all the required items have been included. If an existing map is not available it should be created.

It is important to clearly identify these items so as to be able to respond in an emergency situation.



7.4 PIRMP Review

Review of PIRMP will be undertaken to check that the information is accurate and current and that the plan is capable of being implemented in a workable and effective manner. Reviewing shall be undertaken in the following ways:

- The PIRMP will be tested annually and any identified updates or changes will be made
- The PIRMP will be tested and reviewed within one month from the date of any pollution event that triggers this PIRMP
- The review will also consist of assessment of any additional hazards and control measures
- In addition to site evacuation drills, a mock environmental incident will be done once a year to ensure all site personnel are following training and correct procedures. The mock scenario will be set and all the actions will be captured on the check sheet. Based on these mock incidents, the Site manager and the Environmental Coordinator will review the site personnel preparedness and site procedures to identify gaps or areas for improvement. Records of the drill will be maintained, including follow up of opportunities for improvement identified during emergency drills.


7.5 Typical Holcim Response process

If it is suspected that an incident may cause material environmental harm the Pollution Incident Management Response Plan will be executed. This plan is based on seven phases:

- 1) Assess
- 2) Stop
- 3) Notify
- 4) Contain
- 5) Mitigate
- 6) Clean up
- 7) Review

Details of the requirements and responsibilities for each phase are explained in the following page.





Testing protocol is provided in appendix B

7.6 Communication Strategy

It is a legal requirement of the Protection of the Environment Operations (POEO) Act, to notify key stakeholders in neighbouring properties that may been affected by an incident.

Communicating with neighbours and the community in the event of a spill is vital as they have a right to know about any spill that can potentially lead to material harm to their properties or themselves. The communication strategy in the PIRMP provides sites with a method of communicating with key stakeholders.

Key stakeholders can include neighbouring residential and/or commercial properties, sensitive receivers ie farms, hospitals schools etc. Consideration must be given to sensitive receivers that may be affected if the emission reaches a water body. For example a farmer that is cultivating crops down river from your site will need to be informed of a spill to prevent him spraying his crops with polluted irrigation water.

The PIRMP must include details of the mechanisms that will be used for providing early warnings and regular updates to the owners and occupiers of premises who may be affected by an incident occurring at the premises.

The communication strategy should also make reference to any actions or arrangements that will be in place to minimise the risk of harm to any persons who will be on the premises or who are likely to be on the premises at the time of an incident. This is a legislative requirement that needs to be included in the PIRMP.

For a table detailing the communication strategy for this site:

Refer to Appendix C – Community Notification Strategy

8 Staff Training

Sites need to develop a toolbox talk based on the PIRMP. This training should be delivered to all appropriate personnel on site.

Frequency of training

Training should be repeated annually, and after each update.

How Records of training are kept

Training records should be stored on site and in the Chris 21 data base. The records are to be made available to relevant authorities on request.

9 Continual Improvement

It is a legislative requirement for this plan to be tested and updated on an annual basis and within one month of an incident.

To complete this requirement a Pollution Incident Response Test Checklist has been prepared and provided as Appendix B. The checklist includes the major elements of the plan that require testing:

- Contact numbers
- Evacuation drills
- Desktop assessment
- Environmental controls & PPE

Desktop assessments require site personnel, responsible for testing the plan, to select a scenario from the hazard and impact register (table 2) and ensure that all the required controls for the scenario are in place. During the desktop assessment environmental control and PPE equipment supplies should be inspected to ensure that they are functional and that there are enough materials to ensure that emissions relating to the scenario can be controlled effectively and safely.

Appendix A -Emergency Contact Details

Contacts	Phone Number
Individuals responsible for activating the plans	Quarry Manager
and managing the response	Robert Hewson – 0429 791 071
Individuals Authorised to Notify and Coordinate	Quarry Manager
Relevant Authorities	Robert Hewson – 0429 791 071
Emergency Services	000
EPA	131 555
The Ministry of Health via the local Public Health	Bungendore Medical
Unit	(02) 6299 6990
Department of Mines	(02) 4222 8311
WorkCover Authority	13 10 50
Local Council	Palerang Council
	(02) 6238 8111
Fire and Rescue NSW	Bungendore Fire Dept
	(02) 6297 2332
Other organisations or agencies that need to be	Police
advised of the incident	02 6238 1244

Date: Site 27/11/24

Address 279 Tarago Rd Bungendore:

Pollution Incident Scenario: Oil Spill

Instructions

1. Select an Environmental Incident applicable to the site to test in a Pollution Scenario (this may include a major spill, equipment failure or breaches of license consent that may cause impacts onsite and to the surrounding community);

2. Using the scenario conduct a desktop review using the Test Checklist as a prompt to ensure that each component of the PIRMP is up to date;

3. Sign off the checklist, scan and send to the NSW Planning & Environmental Coordinator;

4. Planning & Environmental Coordinator will make amendments to the plans and submit these to the site managers for review and approval;

5. Site Managers to hold a tool box talk with staff on the details of the PIRMP and keep a copy of the PIRMP onsite for future reference.

	Phone Numbers	
Are all contact details within the plan current and up to date?	Currency	Updated Number
Individuals responsible for activating the plans and managing the response	Robert Hewson	0429791071
Individuals Authorised to Notify and Coordinate Relevant Authorities	Robert Hewson	
Emergency Services	Police	000
EPA		02) 6229 7002
The Ministry of Health via the local Public Health Unit	Bungendore Medical	62381417
WorkCover Authority		48241500
Local Council		

Fire and Rescue NSW	Bungendore	000
Additional Contacts relevant to the licensee's premises	Resources Regulator	
Other Organisations or agencies that need to be advised of the incident		

Environmental Hazards and Control Standards	Yes/ No	Actions
Are the descriptions of environmental hazards up to date?	yes	
Are the potential and likelihood of incidents that could occur still correct and relevant to the site operations?	yes	
Are the pre-emptive actions for risk management of the relevant activity correct and relevant to the site?	yes	
Is there an inventory of pollutants (including quantities of pollutants onsite)?	yes	
Is the listed safety equipment & PPE correct and up to date?	yes	
Is there a map/s located onsite detailing the following; - The site and the surrounding area likely to be affected in the event of an incident - The Locations of storage/ holding points of pollutants - Stormwater drains and discharge points offsite	yes	
Are the nature and objectives of staff training set out in the plan?	yes	
Are there details of mechanisms for providing early warnings and regular updates to the owners and occupiers?	yes	
Is there a copy of the plan onsite and up to date?	yes	

Has there been an evacuation drill in the last 12 months?

Date: 27/11/2024

Notes:

Improvements to the Pollution Incident Response Management Plan:

1)

```
Review complete on the 27/11/24
```

2)

SHE reporting, entering of incidents into Icare

- 3) Emergency response drill
- 4)
- 5)
- 6)

Comments / Recommendations / Review

- 1)
- 2)
- 3)
- 4)

Pollution Incident Response Test Checklist Assessor:

Signed: Quarry Manager

• In an emergency if the spill has the potential to cause harm to the following stakeholders they will be contacted by telephone or alternatively in person.

Adjacent Property	lan Carey	0412 484 615
Elvin group	Chris Rutlidge	02 6241 6461
Adjacent Property	Abbey Morphett	02 6238 1167