

Humes Blacktown Pollution Incident Response Management Plan (PIRMP)

Revision/ Checking History

Revision Number	Date	Checked by	Issued by
1	Nov 2014	Daniel Lidbetter – NSW/ACT Planning & Environment Coordinator	Daniel Lidbetter
2	Nov 2015	Daniel Lidbetter – NSW/ACT Planning & Environment Coordinator	Daniel Lidbetter
3	Nov 2016	Daniel Lidbetter – NSW/ACT Planning & Environment Coordinator	Daniel Lidbetter
4	Oct 2017	Amy Nelson – NSW/ACT Planning & Environment Coordinator Andrew Spence – Business Improvement Manager Max Priebe – Site Operations Manager	Amy Nelson
5	Oct 2018	Hema Vignaraja – SHE Reporting Analyst Max Priebe – Site Operations Manager	Hema Vignaraja
6	Sep 2019	Shilpa Shashi - NSW/ACT Planning & Environment Coordinator Max Priebe – Site Operations Manager	Hema Vignaraja
7	Sep 2020	Shilpa Shashi - NSW/ACT Planning & Environment Coordinator	Shilpa Shashi

8	Nov 2021	Shilpa Shashi - NSW/ACT Planning & Environment Coordinator Max Priebe — Site Operations Manager	Shilpa Shashi
9	Nov 2022	Rob Townsend – Acting Environment Manager – NSW Max Priebe – Site Operations Manager	Rob Townsend
10	Oct 2023	Dozie Egeonu – Environment Manager – NSW & ACT Max Priebe – Site Operations Manager	Dozie Egeonu
11	Nov 2024	Dozie Egeonu — Environment Manager — NSW & ACT Max Priebe — Site Operations Manager	Dozie Egeonu
12	October 2025	Max Priebe – Site Operations Manager	Dozie Egeonu

Table of Contents

1.	Purpose	5
2.	Scope	7
3.	Definitions	7
4.	Associated Documentation	8
5.	Responsibility	8
6.	Record Retention	8
7.	Procedure	9
7.1	Environmental Impact and Hazard Register	9
	Table 1: Holcim SHE Risk Score Matrix	10
	Table 2: Humes Blacktown Environmental Impact and Hazard Register	13
7.2	Pollutant and Safety Equipment Information	16
7.3	Emergency Response Map	38
7.4	PIRMP Review	45
7.5	Typical Holcim Response process	46
7.6	Communication Strategy	48
7.7	Staff Training	49
7.8	Continual Improvement	49

Appendices

- A Emergency Contact Details
- B Pollution Incident Response Test Checklist
- C Community Notification Strategy

Glossary of Acronyms

PIDS- Pollution Information Data Sheet

PPE- Personal Protective Equipment

SDS- Safety Data Sheets

PEOA- Protection of the Environment Operations Act 1997

1. Purpose

The purpose of this document is to detail the pollution incident response management plan for the Humes Blacktown, to comply with Section 5.7A of the Protection of the Environment Operations (POEO) Act:

Protection of the Environment Operations Act 1997 No 156

Part 5.7A Duty to prepare and implement pollution incident response management plans

153A Duty of licence holder to prepare pollution incident response management plan

The holder of an environment protection licence must prepare a pollution incident response management plan that complies with this Part in relation to the activity to which the licence relates.

Maximum penalty:

- (a) in the case of a corporation—\$1,000,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues, or
- (b) in the case of an individual—\$250,000 and, in the case of a continuing offence, a further penalty of \$60,000 for each day the offence continues.

153B EPA may direct other persons to prepare pollution incident response management plan

- (1) The EPA may, in accordance with the regulations, require the occupier of premises at which industry is carried out to prepare a pollution incident response management plan that complies with this Part in relation to activities at the premises.
- (2) A person must not fail to comply with such a requirement.

Maximum penalty:

- (a) in the case of a corporation—\$1,000,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues, or
- (b) in the case of an individual—\$250,000 and, in the case of a continuing offence, a further penalty of \$60,000 for each day the offence continues.
- (3) The regulations may make provision for or with respect to:
 - (a) the class or classes of premises, or industries carried out at premises, that may be the subject of a requirement to prepare a pollution incident response management plan, and
 - (b) the circumstances in which some or all premises within those classes may be the subject of a requirement to prepare a pollution incident response management plan.

153C Information to be included in plan

A pollution incident response management plan must be in the form required by the regulations and must include the following:

- (a) the procedures to be followed by the holder of the relevant environment protection licence, or the occupier of the relevant premises, in notifying a pollution incident to:
 - (i) the owners or occupiers of premises in the vicinity of the premises to which the environment protection licence or the direction under section 153B relates, and
 - (ii) the local authority for the area in which the premises to which the environment protection licence or the direction under section 153B relates are located and any area affected, or potentially affected, by the pollution, and
 - (iii) any persons or authorities required to be notified by Part 5.7,
- (b) a detailed description of the action to be taken, immediately after a pollution incident, by the holder of the relevant environment protection licence, or the occupier of the relevant premises, to reduce or control any pollution
- (c) the procedures to be followed for co-ordinating, with the authorities or persons that have been notified, any action taken in combating the pollution caused by the incident and, in particular, the persons through whom all communications are to be made,
- (d) any other matter required by the regulations.

153D Keeping of plan

A person who is required to prepare a pollution incident response management plan under this Part must ensure that it is kept at the premises to which the relevant environment protection licence relates, or where the relevant activity takes place, and is made available in accordance with the regulations.

Maximum penalty:

- (a) in the case of a corporation—\$1,000,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues, or
- (b) in the case of an individual—\$250,000 and, in the case of a continuing offence, a further penalty of \$60,000 for each day the offence continues.

153E Testing of plan

A person who is required to prepare a pollution incident response management plan under this Part must ensure that it is tested in accordance with the regulations.

Maximum penalty:

- (a) in the case of a corporation—\$2,000,000 and, in the case of a continuing offence, a further penalty of \$240,000 for each day the offence continues, or
- (b) in the case of an individual—\$500,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues.

153F Implementation of plan

If a pollution incident occurs in the course of an activity so that material harm to the environment (within the meaning of section 147) is caused or threatened, the person carrying on the activity must immediately implement any pollution incident response management plan in relation to the activity required by this Part.

Maximum penalty:

- (a) in the case of a corporation—\$2,000,000 and, in the case of a continuing offence, a further penalty of \$240,000 for each day the offence continues, or
- (b) in the case of an individual—\$500,000 and, in the case of a continuing offence, a further penalty of \$120,000 for each day the offence continues.

2. Scope

The scope of this management plan includes:

Pollution Incident Response Management Plan (PIRMP) for environmental pollution generated at the Teven;

3. Definitions

Pollution Incident -

An incident or set of circumstances during or as a consequence of which there is or is likely to be a leak, spill or other escape or deposit of a substance, as a result of which pollution has occurred, is occurring or is likely to occur. It includes an incident or set of circumstances in which a substance has been placed or disposed of on premises, but it does not include an incident or set of circumstances involving only the emission of any noise.

Material Harm -

- (i) it involves actual or potential harm to the health or safety of human beings or to ecosystems that is not trivial, or
- (ii) it results in actual or potential loss or property damage of an amount, or amounts in aggregate, exceeding \$10,000 (or such other amount as is prescribed by the regulations), It does not matter that harm to the environment is caused only in the premises where the pollution incident occurs, and

the reasonable costs and expenses that would be incurred in taking all reasonable and practicable measures to prevent mitigate or make good harm to the environment.

4. Associated Documentation

- Protection of the Environment Operations Act 1997
- Protection of the Environment (General) Amendment (Pollution Incident Response Management Plans) Regulation 2012
- Appendix A: Emergency Contact Details
- Appendix B: Pollution Incident Response Test Checklist
- Appendix C: Community Notification Strategy

5. Responsibility

The following personnel are responsible for the PIRMP;

- Activating the plans and managing the response: Max Priebe Site Operations
 Manager
- Notifying and coordinating relevant authorities: Max Priebe Site Operations
 Manager
- 3) Implementation and management of this document: Max Priebe Site Operations
 Manager
- 4) Annual review and test of PIRMP- Max Priebe Site Operations Manager

6. Record Retention

A copy of all Quarry pollution incident response records will be retained on site in accordance with SHE guideline 1.4 – Administrative and Legal Requirements. A copy will also be saved electronically on google drive in the 'Site PIRMPs Final' folder and linked with the site's SHE schedule.

Records must be made available to EPA officers and any person responsible for the PIRMP.

7. Procedure

The following section outlines the management procedures for pollution incident response management. The protocol is split into three sections:

- 1) Key environmental hazards and mitigation measures
- 2) Pollutant and Safety equipment information and management of Pollution Incidents
- 3) Emergency Response Maps

7.1 Environmental Impact and Hazard Register

In order to effectively plan for a potential pollution event, a register of environmental hazards has been created. Each hazard has been assessed in accordance with the Holcim SHE Risk Assessment tool (see Table 1 below).

The hazards have been grouped according to the area of environmental impact. By identifying these hazards ahead of time, mitigation measures can be identified and implemented through site procedures to minimise the risk of a pollution event occurring (table 2 below).

Table 1: Holcim SHE Risk Score Matrix

Step 1 - Consider the Consequence

What are the consequences of the most reasonable worst case scenario considering a credible failure of existing controls?

Consequence	Disaster	Severe	Serious	Significant	Minor
Environment On Site & Off Site	Major event, unconfined impact, severe permanent damage with low likelihood of recovery.	Significant permanent damage; reversible damage with recovery time of years; high potential for prosecution	Minor permanent damage; temporary damage that is widespread or that has moderate impact	Damage that is near source confined, temporary and minor	No measurable damage to environment
Compliance With Legal and Other Requirements	Blatant or serious breach of legal requirement, leading to operation being suspended or severely reduced. Prosecution expected.	Breach of external requirement (license, legislation, regulation, contract etc.) with high potential for prosecution and/or high impact.	Non-compliance with external requirement with moderate potential for impact.	Repeated non-compliance with internal procedure, non-compliance with external requirement with low potential impact	Minor non-compliance with internal procedures.

Community (s Perception le and Reputation re	Significant adverse media attention (state or national level), loss of reputation or work nationally or across product groups. Prosecution, signification impacts on social lice to operate, loss of reputation or ability secure work across product groups.	reputation or ability to	Multiple community complaints or complaints that require changes to internal operating procedures.	Community complaint resolved with no changes to existing operating procedures.
--	--	--------------------------	--	--

Note: Temporary environmental damage has a duration of up to approximately one week to rectify

Step 2 - Consider the Likelihood											
What is the likelihood that the proposed consequence will occur with a credible failure of existing controls?											
Likelihood	Certain	Likely	Possible	Unlikely	Rare						
Description	Event that is expected to occur on multiple occasions	occur Event that is likely to occur at least once		Event that is unlikely to occur	Event that may occur only in exceptional circumstances						
Frequency	Event is likely to occur more than twice a year.	Event is likely to occur once or twice a year.	Event is likely to occur more than once or twice in a 10 year period	Event is likely to occur once or twice in a 10 year period	Event is likely to occur once or twice in a 100 year period						

Step 3 - Determine Risk Rating from the Risk Matrix

Liklihood			Consequences		
Liklihood	Disaster	Severe	Serious	Significant	Minor
Certain	High	High	High	Medium	Medium
Likely	High	High	Medium	Medium	Low
Possible	High	Medium	Medium	Low	Low
Unlikely	Medium	Medium	Low	Low	Low
Rare	Medium	Low	Low	Low	Low

Table 2: Humes Blacktown Environmental Impact and Hazard Register

V av	Key Environmental Hazards		Risk		Balai
Key			С	R	Mitigation Measures
			_		
1	Excessive dust emissions		S		
		U	i		
		n	g		
		l ;	n		
		i	i	L	Water carts/spraying
		k	f	0	Stop dust generating activities as necessary
		е	i	w	
		ı	С		
		У	а		
			n		
2	Health issues off site		t S		
2	Health issues on site		3 i		
			g		
			n B		
		R	''	L	
		а	f	0	- As per (1)
		r	i w		
		е			
			а		
			n		
			t		

8 GI 1	Equipment exhaust emissions exceed limits roundwater Groundwater contamination	R a r e R a r e	M i n o r S e r i o	L o w		All equipment is serviced and maintained Excessive equipment emissions to trigger out of service procedures Implement Monitoring and response plan Ensure storage, handling and transport of dangerous goods are conducted in accordance with Australian Standards Identify, classify, quantify & appropriately store hazardous waste Develop & implement oil & fuel spillage controls Ensure hazardous waste is minimised Licenced contractors to remove hazardous waste from site Keep records of all hazardous waste movements
1	Discharge of sediment	P 0 s s i b l e	u s S e r i o u s	M e d i u m	• • • • • • • • • • • • • • • • • • • •	Implement bunding to appropriate areas Ensure adequate spill kits are available on site including adequate training Minimise hazardous waste storage quantities on site Develop & implement Water Management Plan Implement Monitoring Program Review monitoring results quarterly & action as necessary Develop & implement Surface & Groundwater Response Plan

2	Discharge of hazardous materials	R a r e	S e v e r e	L o w		Ensure storage, handling and transport of dangerous goods are conducted in accordance with relevant Australian Standard Identify classify, quantify & appropriately store hazardous waste Develop & implement oil & fuel spillage controls Implement bunding to appropriate areas Ensure adequate spill kits are available on site including adequate training for effective use Minimise hazardous waste storage quantities on site Appropriate location of hazardous materials storage areas to prevent off-site discharges
1	Damage to site fauna	U n i k e I y	S e r i o u s	R a r e	-	As per 1 Information re local WIRES for distressed or injured fauna
1	Spill of liquid fuel whilst in storage	R a r e	S e r i o u s	L o w	•	Fuels stored according to Holcim's bunding requirements. Measures in place to ensure spills do not leave site boundaries ie diverting flow away from boundaries, stormwater drains. Bunding subject to regular inspection and maintenance

3	Spill during delivery of fuel to mobile equipment Spill during delivery of fuel to storage tank	P o s s i b l e P o s s	S e v e r e	M e d i u m	Emergency spill kits located on fuel delivery vehicles. Spill response equipment is regularly inspected and maintained Mobile refuelling takes place in the pit Drivers trained in spill response procedures. Refuelling takes place in designated refuelling areas. Supplier's fuel transfer procedure is known
		i b I e	e r e	i u m	
4	Improper storage of cementitious materials	L k e I y	S i g n i c a n t	M e d i u m	Quantities held on site are minimised or capped Location of stockpiles close to processing point Cementitious materials are managed in accordance with approval conditions

6	Land contamination		S		•	Holcim land contamination strategy is known and applied
			i			
		.	g	N 4		
		-	n	M		
		İ	il	е		
		k	f	d		
		e	¦	i		
		1	'.	u		
		y	c	m		
		<i>'</i>	a			
			n			
			t			

7.2 Pollutant and Safety Equipment Information

Legislative requirements under the Protection of the Environment Operations (POEO) Act dictate that the site is to provide information for all pollutants that are used and stored on the site. This information is required as it assists personnel responsible for coordinating spill responses to more effectively manage spills.

This information must be presented as a manifest detailing the pollutants stored at the site, the location of these storage areas, and the safety equipment to be made available at these areas. A Pollution Information Data Sheet (PIDS) has been prepared that includes the following information for each pollutant. Refer to table 3 below

- The intended use for the pollutant
- How the pollutant is stored
- SDS information
- Safety equipment or other devices that are used to minimise the risks to human health or the environment and to contain or control a pollution incident
- PPE needed to safely manage a spill of the pollutant
- Procedure for cleaning up a spill of the pollutant.

In order to ensure the currency and reliability of the information in the PIDS, the information should be reviewed and updated on a monthly basis.

 Table 3: Pollutant Information Data Sheet and clean-up methods

Pollutant	Storage	Current	Emission	PPE (1)	
	Location	SDS	control		Spill Clean Up Method (1)
		held	equipment		Spin clean of Method (1)
		Yes/No	(1)		
Fuel	Front of maintenance	Yes	Sand, earth,	PVC gloves, safety glasses,	Large Spill
	workshop –		vermiculite	goggles, steel	<u>Assess</u>
	Diesel Tank			cap boots and respirator	Quickly assess the spill:
	Maintenance			mask	Decide whether to handle the situation by yourself or if you require help.
	chemical				Advise your team of the hazard
	storage				Post a guard or barricade
					Can you stop the source of the spill?
	Flammable				
	Liquid				Ensure Personal Safety
	Cabinet in				
	Precast				First priority is to ensure safety of yourself and others in the area
					Consider evacuation and isolation.
					Do you or others require PPE
					Check Safety Data Sheet
					<u>Secure</u>

		Secure the spill If hazardous to public or other staff exists Post a guard immediately Enter barricades to prevent unintended access
		Contain Contain the spill quickly by surrounding with the booms which should be firmly secured in place. Find the source of the leak and stop it Emergency stop, cap, plug, move, adjust Move other containers from that area to a bunded area In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment.
		Prevent Prevent spillage to stormwater drains and entry into sewer, water courses, basements or confined areas. Absorb

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Recover product from the surface. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor **Disposal** Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked and placed in a leak proof container which is locked. SDS should be made available. Reporting Incident and Corrective and Preventative action should be captured on the ICare. **Small Spill** Stop leak without risk.

					Move containers from spill area Absorb with an inert material and place in appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
Lubricants & vehicle fluids	Maintenance Precast Bund	Yes	Sand, earth, vermiculite, barrier equipment (booms, floats etc.)	PVC Gloves, safety glasses, goggles	Large Spill Assess Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard Post a guard or barricade Can you stop the source of the spill? Ensure Personal Safety First priority is to ensure safety of yourself and others in the area Consider evacuation and isolation. Do you or others require PPE Check Safety Data Sheet

		<u>Secure</u>
		Secure the spill If hazardous to public or other staff exists Post a guard immediately Enter barricades to prevent unintended access
		<u>Contain</u>
		Contain the spill quickly by surrounding with the booms which should be firmly secured in place. Find the source of the leak and stop it Emergency stop, cap, plug, move, adjust Move other containers from that area to a bunded area
		In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment.
		Prevent Prevent spillage to stormwater drains and entry into sewer, water courses, basements or confined areas.
		<u>Absorb</u>

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Recover product from the surface. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor Disposal Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked and placed in a leak proof container which is locked. SDS should be made available. Reporting

					Incident and Corrective and Preventative action should be captured on the ICare.
					Small Spill
					Stop leak without risk.
					Move containers from spill area
					Absorb with an inert material and place in appropriate waste disposal container.
					Use spark-proof tools and explosion-proof equipment.
					Dispose of via a licensed waste disposal contractor.
					Large Spill
Truck wash	Store	Yes	Sand,	PVC Gloves,	
			earth,	safety glasses	<u>Assess</u>
			vermiculite		Quickly assess the spill:
					Decide whether to handle the situation by yourself or if you require help.
					Advise your team of the hazard
					Post a guard or barricade
					Can you stop the source of the spill?

Ensure Personal Safety First priority is to ensure safety of yourself and others in the area Consider evacuation and isolation. Do you or others require PPE Check Safety Data Sheet **Secure** Secure the spill If hazardous to public or other staff exists Post a guard immediately Enter barricades to prevent unintended access **Contain** Contain the spill quickly by surrounding with the booms which should be firmly secured in place. Find the source of the leak and stop it Emergency stop, cap, plug, move, adjust Move other containers from that area to a bunded area In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment.

Prevent Prevent spillage to stormwater drains and entry into sewer, water courses, basements or confined areas. **Absorb** Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Recover product from the surface. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor **Disposal** Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked and placed in a leak proof container which is locked. SDS should be made available. Reporting

					Incident and Corrective and Preventative action should be captured on the Icare. Small Spill Stop leak without risk. Move containers from spill area Dilute with water and mop up, or absorb with an inert dry material and place in appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Corrosives	Pipes Bund B1 & B2 Machines	Yes	Sand, earth, vermiculite	PVC Gloves, safety glasses, goggles, overalls. Use respirator if there is a significate risk	Accidental release Assess First priority is to ensure safety of yourself and others in the area Consider evacuation and isolation. Do you or others require PPE Check Safety Data Sheet

Г			
		of vapours or	In the event of a major spill, prevent spillage from entering drains or water courses.
		mist.	
			Evacuate the spill area and deny entry to unnecessary and unprotected personnel.
			Immediately call the relevant authorities.
			Ensure Personal Safety
			Wear full protective clothing including eye/face protection.
			All skin areas should be covered.
			Stop leak if safe to do so, and contain the spill.
			Co anno
			<u>Secure</u>
			Secure the spill
			If hazardous to public or other staff exists
			Post a guard immediately
			Enter barricades to prevent unintended access
			Absorb onto sand, vermiculite or other suitable absorbent material.
			If the spill is too large try to create a dike to stop material spreading or going into drains or water-ways
			Contain and Disposal

					Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose promptly. Dispose of via a licensed waste disposal contractor. If it is possible that material harm to the environment has occurred relevant personnel should be contacted Reporting Incident and Corrective and Preventative action should be captured on the ICare.
Release Agents	Precast Bund @ G2 Pipes Bund G4 G2 near lunchroom	Yes	Soil, Sand, vermiculite or other inert materials	PVC Gloves, safety glasses	Accidental release Assess First priority is to ensure safety of yourself and others in the area Consider evacuation and isolation. Do you or others require PPE Check Safety Data Sheet Remove all sources of ignition.

B2		In the event of a major spill, prevent spillage from entering drains or water courses.
		Evacuate the spill area and deny entry to unnecessary and unprotected personnel.
		Immediately call the relevant authorities.
		Ensure Personal Safety
		Wear full protective clothing including eye/face protection.
		All skin areas should be covered.
		Avoid inhalation.
		Stop leak if safe to do so, and contain the spill.
		<u>Secure</u>
		Secure the spill
		If hazardous to public or other staff exists
		Post a guard immediately
		Enter barricades to prevent unintended access
		Absorb onto sand, vermiculite or other inert material.
		If the spill is too large try to create a dike to stop material spreading or going into drains or water-ways
		Use absorbent (soil, sand or other inert material).

	Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose promptly. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor. If it is possible that material harm to the environment has occurred relevant personnel should be contacted Reporting Incident and Corrective and Preventative action should be captured on the ICare. Small Spill Contain spillage Avoid breathing vapours and contact with skin and eyes Control contact using PPE Wipe up with absorbent (clean rag or paper towels) Collect and seal in properly labelled containers or drums for disposal.
	Collect and seal in properly labelled containers or drums for disposal.

Herbasides	Stores G2 near lunch room on portable bund	Yes	Sand, earth or absorbent material	PVC Gloves, safety glasses	Assess First priority is to ensure safety of yourself and others in the area Consider evacuation and isolation. Do you or others require PPE Check Safety Data Sheet In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the relevant authorities.
					Ensure Personal Safety Wear full protective clothing including eye/face protection. All skin areas should be covered. Stop leak if safe to do so, and contain the spill. Secure

Secure the spill If hazardous to public or other staff exists Post a guard immediately Enter barricades to prevent unintended access Absorb onto sand, vermiculite or other suitable absorbent material. If the spill is too large try to create a dike to stop material spreading or going into drains or water-ways **Contain and Disposal** Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose promptly. Dispose of via a licensed waste disposal contractor. If it is possible that material harm to the environment has occurred relevant personnel should be contacted Reporting Incident and Corrective and Preventative action should be captured on the ICare.

					Small Spills Contain spillage Avoid breathing vapours and contact with skin and eyes Control contact using PPE Contain and absorb with sand, earth, inert material, vermiculite etc. Flush spill area with water.
Hardeners and Resins	Maintenance Pipes Store Precast G2 Pipes Lab	Yes	Sand, earth, vermiculite	Safety glasses, PVC gloves, Respirator	Large Spill Assess Quickly assess the spill: Decide whether to handle the situation by yourself or if you require help. Advise your team of the hazard Post a guard or barricade Can you stop the source of the spill? Ensure Personal Safety

	First priority is to ensure safety of yourself and others in the area
	Consider evacuation and isolation
	Do you or others require PPE
	Check Safety Data Sheet
	Secure
	Secure the spill
	If hazardous to public or other staff exists
	Post a guard immediately
	Enter barricades to prevent unintended access
	· ·
	<u>Contain</u>
	Contain the spill quickly by surrounding with the booms which should be firmly secured in place.
	Find the source of the leak and stop it
	Emergency stop, cap, plug, move, adjust
	Move other containers from that area to a bunded area
	INIOVE OTHER CONTAINERS FROM CHIEF ALEA TO A DUNIQUE ALEA
	In the case of spillage on water provent the spread of product by the use of suitable barrier equipment
	In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment.
	Duranet
	<u>Prevent</u>

Prevent spillage to stormwater drains and entry into sewer, water courses, basements or confined areas. **Absorb** Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Recover product from the surface. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor **Disposal** Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place into a container according to local legislation. Use spark-proof tools and explosive proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Monitor its disposal. The spill soiled bags need to be labelled and ear marked and placed in a leak proof container which is locked. SDS should be made available. Reporting Incident and Corrective and Preventative action should be captured on the ICare.

					Minor Spills Contain spillage Avoid breathing vapours and contact with skin and eyes Control contact using PPE Contain and absorb with sand, earth, inert material, vermiculite etc. Small spills should be covered with inorganic absorbents and disposed of properly. Organic absorbents (ie. sawdust) may ignite when contaminated with amines in closed containers
Dry Powders	Precast G2 Pipes Lab B1 Outramp B2 Outramp Silo	Yes	Access to council sweeper, soil, sand, vermiculite	Safety glasses, PVC Gloves,	Accidental Release Measures Emergency procedures: Prevent entry to area by unprotected personnel. Methods and material for containments and clean up 1) Vacuum or wet sweep material avoiding generation of dusts. 2) A fine water spray should be used to suppress dust when sweeping. 3) Product dampened with water may be collected with a clean shovel. 4) Seal all spilled product and wastes in vapour tight labelled plastic containers for reuse/recycle where possible or eventual disposal.

Welding gas	Pipes Silo	Yes	Ventilation	Respirator	Occupational Release:
	Precast Structural				1) Avoid heat, flames, sparks and other sources of ignition.
	Lane				2) Stop leak if possible without personal risk.
	Precast Reo				3) Reduce vapours with water spray4) Keep unnecessary people away, isolate hazard area and deny entry.5) Remove sources of ignition.
	Maintenance Workshop				6) Ventilate closed spaces before entering.

^{7.6} $_{(1)}$ This information is drawn from a review of the SDS or manufacturer/supplier technical information

7.3 Emergency Response Map

In addition to the PIDS the site needs to prepare an emergency response map that provides the following information;


- address of site
- location of pollutant storage
- location of safety equipment
- emergency evacuation / muster points
- stormwater drains / flow paths
- sensitive receivers
- sediment dam overflow locations
- location of SDS
- surrounding area that is likely to be affected by a pollution incident
- discharge location of stormwater drains to nearest water coarse or water body


Existing site maps that have been developed to comply with Holcim SHE system requirement 1.84 may be used if all the required items have been included. If an existing map is not available it should be created.


Issue date: October 2025


It is important to clearly identify these items so as to be able to respond in an emergency situation.

SURROUNDING AREA LIKELY TO BE AFFECTED










.



7.4 PIRMP Review

Review of PIRMP will be undertaken to check that the information is accurate and current and that the plan is capable of being implemented in a workable and effective manner. Reviewing shall be undertaken in the following ways:

The PIRMP will be tested annually and any identified updates or changes will be made. The PIRMP will be tested and reviewed within one month from the date of any pollution event that triggers this PIRMP. The review will also consist of assessment of any additional hazards and control measures.


In addition to site evacuation drills, a mock environmental incident will be done once a year to ensure all site personnel are following training and correct procedures. The mock scenario will be set and all the actions will be captured on the check sheet. Based on these mock incidents, the Site manager and the Planning and Environmental Coordinator will review the site personnel preparedness and site procedures to identify gaps or areas for improvement. Records of the drill will be maintained, including follow up of opportunities for improvement identified during emergency drills.

7.5 Typical Holcim Response process

If it is suspected that an incident may cause material environmental harm the Pollution Incident Management Response Plan will be executed. This plan is based on seven phases:

- **1.** Assess
- **2.** Stop
- **3.** Notify
- **4.** Contain
- **5.** Mitigate
- **6.** Clean up
- **7.** Review

Details of the requirements and responsibilities for each phase are explained below.



Close open valve causing spill

49

te: October 2025

Notify

•Contact key individuals

- •Individuals responsible for activating and managing plans (nominated site representatives)
- •Individuals authorised to notify and coordinate relevant authorities (nominated site representatives)

•Contact Relevant Authorities

- •Firstly, call 000 if the incident presents an immediate threat to human health or property.
- If the incident does not require an initial combat agency, or once the 000 call has been made, notify the relevant authorities in the following order. The 24-hour hotline for each authority is given when available:
- •the Appropriate Regulatory Authority
- EPA
- •Ministry of Health via the local Public Health Unit
- WorkCover Authority
- •the local authority if this is not the ARA
- •Fire and Rescue NSW

•Specific contact details are provided in appendix A

e date: October 2025

Contain

- Utilise barriers (absorbent booms, banks of soil or any other safe objects) or spill absorbent to prevent the emission from spreading.
- •When an emission is on a hard surface use appropriate absorbent materials ie absorbent granules or sand
- •The main priority is to prevent the emitted material from discharging off site

Mitigate

- •Implement environmental controls downstream of pollution source to prevent/minimise further impact to receiving environment
- Example:
- A Fuel spill discharged into quarry dam. Mitigation controls to ensure this spill is not spread may include closing of weirs, or outlets, ensuring water cart does not fill from affected dam etc.

Clean -up

- Clean up and remedial actions to restore the environment
- Disposal of pollutants in accordance with regulations
- Refer to the Pollution Information Data Sheets (PIDS) for information on handling pollutants and the clean-up process.

- Conduct an investigation into the event and assist the EPA and investigators with external enquiries
- Complete internal reporting;
- As per Holcim SHE requirement 5.1
- •Test the effectiveness of Pollution Incident Response Management Plan annually and one month after the incident to ensure controls are replenished.
- Testing protocol is provided in appendix B

7.6 Communication Strategy

It is a legal requirement of the Protection of the Environment Operations (POEO) Act, to notify key stakeholders in neighbouring properties that may been

affected by an incident.

Communicating with neighbours and the community in the event of an environmental incident is vital as they have a right to know about any spill that

can potentially lead to material harm to their properties or themselves. The communication strategy in the PIRMP provides sites with a method of

communicating with key stakeholders.

Key stakeholders include neighbouring residential and/or commercial properties, sensitive receivers ie farms, hospitals schools within the area of impact.

Consideration must be given to sensitive receivers that may be affected if the emission reaches a water body. For example a farmer that is cultivating

crops down river from your site will need to be informed of a spill to prevent him spraying his crops with polluted irrigation water.

The PIRMP must include details of the mechanisms that will be used for providing early warnings and regular updates to the owners and occupiers of

premises who may be affected by an incident occurring at the premises.

The communication strategy should also make reference to any actions or arrangements that will be in place to minimise the risk of harm to any persons

who will be on the premises or who are likely to be on the premises at the time of an incident. This is a legislative requirement that needs to be included

Issue date: October 2025

in the PIRMP.

For a table detailing the communication strategy for this site:

Refer to Appendix C – Community Notification Strategy

53

7.7 Staff Training

Sites need to develop a toolbox talk based on the PIRMP. This training should be delivered to all appropriate personnel on site and be conducted to include potential scenarios that may require implementation of the plan.

Frequency of training

Training for site staff should be repeated annually, and after each update to the plan. In the event of an incident requiring the PIRMP to be activated a training drill should be carried within one month of the incident occurring.

How Records of training are kept

Training records should be stored on site and in the Rapid Induct data base. This data base is the primary online tool for tracking individual staff training records and frequency for training and refresh courses. These records are to be made available to relevant authorities on request.

7.8 Continual Improvement

It is a legislative requirement for this plan to be tested and updated on an annual basis and within one month of an incident.

To complete this requirement a Pollution Incident Response Test Checklist has been prepared and provided as Appendix B. The checklist includes the major elements of the plan that require testing:

- Contact numbers
- Evacuation drills
- Desktop assessment
- Staff training and awareness
- Environmental controls & PPE

Desktop assessments require site personnel, responsible for testing the plan, to select a scenario from the hazard and impact register (table 2) and ensure that all the required controls for the scenario are in place. During the desktop assessment environmental control and PPE equipment supplies should be inspected to ensure that they are functional and that there are enough materials to ensure that emissions relating to the scenario can be controlled effectively and safely.

Appendix A Emergency Contact Details

Contacts	Phone Number	
Individuals responsible for activating the plans	Site Operations Manager	
and managing the response	Max Priebe	
	0419 475 776	
Individuals Authorised to Notify and Coordinate Relevant Authorities	Site Operations Manager	
	Max Priebe	
	0419 475 776	
Emergency Services	000	
EPA	131 555	
The Ministry of Health via the local Public Health	Westmead Hospital	
Unit	(02) 8890 5555	
WorkCover Authority	13 10 50	
Local Council	Blacktown City Council	
	(02) 9839 6000	
Fire and Rescue NSW	(02) 9625 4403	
Additional Contacts relevant to the licensee's	Charlie Breia	
premises	Area Manager NSW	
	0419 476 491	
Spill Contractor	JR Waste & Recycling	
Spin contractor	Laurie Maher	
	0427 450 517	

Appendix B Pollution Incident
Response Test
Checklist

Date:14/09/2025
Site:Humes Blacktown
Address:Lot 1 604 Woodstock Ave, Rooty Hill, NSW, 2766
Pollution Incident Scenario:Waste Oil Drum Spill
Instructions

- 1. Select an Environmental Incident applicable to the site to test in a Pollution Scenario (this may include a major spill, equipment failure or breaches of license consent that may cause impacts onsite and to the surrounding community);
- 2. Using the scenario conduct a desktop review using the Test Checklist as a prompt to ensure that each component of the PIRMP is up to date;
- 3. Sign off the checklist, scan and send to the NSW Planning & Environmental Coordinator;
- 4. Planning & Environmental Coordinator will make amendments to the plans and submit these to the site managers for review and approval;
- 5. Site Managers to hold a tool box talk with staff on the details of the PIRMP and keep a copy of the PIRMP onsite for future reference.

Are all contact details within the plan current and up to date?	Phone Numbers	
	Currency	Updated Number
Individuals responsible for activating the plans and managing the response	Yes	Max Priebe Operations Manager 0419 475 776
Individuals Authorised to Notify and Coordinate Relevant Authorities	Yes	As Above

Emergency Services	Yes	000
EPA	Yes	131 555
The Ministry of Health via the local Public Health Unit	Yes	Westmead Hospital 02 8890 5555
WorkCover Authority	Yes	13 10 50
Local Council	Yes	Blacktown City Council 02 9839 6000
Fire and Rescue NSW	Yes	02 9625 4403
Additional Contacts relevant to the licensee's premises	Yes	Charlie Breia Area Manager 0419 476 491
Other Organisations or agencies that need to be advised of the incident	N/A	

Environmental Hazards and Control Standards	Yes/ No	Actions
Are the descriptions of environmental hazards up to date?	Yes	
Are the potential and likelihood of incidents that could occur still correct and relevant to the site operations?	Yes	

Are the pre-emptive actions for risk management of the relevant activity correct and relevant to the site?	Yes	
Is there an inventory of pollutants (including quantities of pollutants onsite)?	Yes	
Is the listed safety equipment & PPE correct and up to date?	Yes	
Is there a map/s located onsite detailing the following;	Yes	
- The site and the surrounding area likely to be affected in the event of an incident		
- The Locations of storage/ holding points of pollutants		
- Stormwater drains and discharge points offsite		
Are the nature and objectives of staff training set out in the plan?	Yes	
Are there details of mechanisms for providing early warnings and regular updates to the owners and occupiers?	Yes	
Is there a copy of the plan onsite and up to date?	Yes	

Has there been an evacuation drill in the last 12 months? Yes

Date: 28th August 2025

Notes: Site cleared in 15 minutes. Well managed. Effective communication. Construction site evacuated as part of drill.

Improvements to the Pollution Incident Response Management Plan:

•

Comments / Recommendations / Review

- Reviewed and adjusted Pollutants
- SDS register reviewed and updated yearly
- Environmental Hazards and Controls reviewed and accurate
- Map reviewed and adjusted to include all SDS locations, discharge points and impacts area

Pollution Incident Response Test Checklist Assessor: Max Priebe

Signed: Max Priebe

Spill Scenario Checksheet

Date: 14 9.25 Site: Blacktown. Address: Lot I woodstock Ave. Rooty) Brief Description of Spill Scenario:	a lilla	ma with
Duna O	7	0000
pump	V	0
*		
Spill Response Sequence	Ti	me
	Hours	Minutes
Scenario Started	2	: 30
Spill Discovered and Alarm Raised	21	: 35
Spill Assessed	21	: 40
Source of Spill Stopped or Restricted	21	: 40
Spill Contained	21	: 50
Spill Reported to Site Management	21	: 53_
Spill Cleaned Up	22_	: 45
Spill Clean Up Materials Disposed of Appropriately	22	: SO
All personnel present at the time of the scenario exercise should partic cannot participate, this should be noted in the comments section and the requirements should be verbally checked.	ipate Where p heir knowledge	personnel on emergency
Comments / Recommendations / Review / Improvements: Check ou level in drum be	leve ad	ding
contact on drum.	amtan	ege_
Spylboss natural abnorbent us wasteoil from floor.	ed to d	lean up
then placed inside of iBC container	to be	removed
Observer (name): DALE SHARWOOD Signed:		

Appendix C – Community Notification Strategy

If there is an Environmental Incident that has the potential to cause harm to the following stakeholders they will be contacted by TELEPHONE

Stakeholder Component	Name	Contact Information
Nearby Property (Upstream)	Infrabuild Steel – Rooty Hill	(02) 9675 9999 22 Kellogg Rd, Rooty Hill
Nature Reserve (Downstream)	Nurrangingy Reserve	Blacktown City Council (02) 9839 6000 Nurrangingy Reserve, Knox Road, Doonside (Site personnel will visit the reserve after a pollution incident to give guidance to the general public if there is a potential risk of harm to persons or property in the area)
Nearby Property (Downwind)	Cleanaway	Bhavin Rao 0498 570 640
Nearby Property (Downwind)	Nexport (Currently being demolished)	1800 639 7678
Nearby Property (Downwind)	Holcim Australia- Rooty hill Distribution Centre	Michael Ensor 0419 476 052
Nearby Property (Downwind)	Holcim Concrete	James Calvert 0432 694 199